


Synergy 21 LED Flex Strip 60 NW DC12V 72W IP20 CRI>90



Abbildung ähnlich



kwh/1000h:	72,00
Lumens:	4500
Watt:	72,0
Nominal Service Life:	35000 Std.
Switching Cycles:	50000
Opt. Ambient Temperature.:	25 °C



LED Flex Strip neutral white, PCB white
DC12V, max. 6A, 72W \pm 10%,
300Leds, 120°, 5050SMD,
CRI>90
can be shortened every 3 LEDs (50mm)
Length: 5000*10*3mm,
lumen: 4500
4250K \pm 250
indoor
open cable end
Adhesive tape for mounting aid on the back
Energy efficiency class: A
kWh/1000h: 72

Please note that LED strips also need to be cooled.

Make sure that the LED strip does not exceed the working temperature of 40°C, otherwise the service life cannot be guaranteed.

Attributes

Attribute	Value
Abstrahlwinkel:	120

Attribute	Value
Ampere:	6
CC oder CV:	CV
CRI:	>90
Dimmbar:	abhängig vom Netzteil
Länge:	5
LED Strip Klebeband:	ja
LED Strip Breite:	10
LED Strip Höhe:	3
LED Strip Klebeband:	ja
LED Strip kürzbar:	50
LED Strip Länge:	5000
Lichtfabe in Kelvin:	4250
Lichtfarbe:	neutralweiß
Lichtfarbe in Kelvin:	4250
Lichtfarbe Name:	neutralweiß
Lumen:	4500
Schutzklasse:	IP20
Volt:	12
Weight:	0.1 Kg

Accessories

Part No.	Name
81069	Synergy 21 LED zub Hollow Socket with Screw Terminals
81068	Synergy 21 LED zub wooden plug with screw terminals
81741	Synergy 21 LED Flex Strip add. Silicone mounting clip 10 pack
89592	Synergy 21 Power supply - 12V 96 Watt
139522	Mean Well power supply - 12V 120W IP67