



Synergy 21 LED Flex Strip 280 WW DC24V 196W IP65 ULS 20m



kwh/1000h:	215,60
Lumens:	19800
Watt:	196,0
Nominal Service Life:	35000 Std.
Switching Cycles:	50000
Opt. Ambient Temperature.:	25 °C



Synergy 21 LED Flex Strip ULS Series
ULS=Ultra Long Strip

Voltage: 24V,
Watt: 196W
CRI>80
Light colour: warm white, 3000K
Brightness: 19800lm, 990l/m
Beam angle: 120°
Protection class: IP65
Number of LEDs: 70/m
Dimensions: 20000*10*3 mm
PCB colour: white, open cable end (360±5mm)
Operating temperature: -25°C to +40°C
Weight: 0.500kg
Can be shortened every 7 LED 10cm
Adhesive tape: no

Energy efficiency class: A+
kWh/1000h: 215.6

Strip can be shortened at the cut marks with sharp scissors.
!Attention! Strip must first be checked for functionality.
Only split the strip when no current is present.


Our 3M adhesive tape adheres well, but should only be used as a mounting aid.
There are a variety of mounting options, such as clips, permanently elastic mounting adhesive, cable ties, etc.

Please note that LED strips must also be cooled.
Make sure that the LED strip does not exceed a working temperature of 40°C, otherwise its service life cannot be guaranteed.
No guarantee can be given for overheated LED strips

Attributes

Attribute	Value
Abstrahlwinkel:	120
Ampere:	8.20
CC oder CV:	CV
CRI:	>80
Dimmbar:	abhängig vom Netzteil
LED Strip Klebeband:	ja
LED Strip Breite:	10
LED Strip Höhe:	3
LED Strip kürzbar:	100
LED Strip Länge:	20000
Lichtfabe in Kelvin:	3000
Lichtfarbe:	warmweiß
Lichtfarbe in Kelvin:	3000
Lichtfarbe Name:	warmweiß
Lumen:	19800
Schutzklasse:	IP65
Volt:	24
Weight:	0.5 Kg
Warranty:	60.00 Months

Additional Images



Accessories

Part No.	Name
125198	Mean Well Power Supply - 24V 150W IP67