
Part No.: 133000

Vendor Part No.: S21-LED-F00098

Synergy 21 LED Flex Strip 60 red DC24V 24W IP20





kwh/1000h:	24,00
Lumens:	2025
Watt:	24,0
Nominal Service Life:	35000 Std.
Switching Cycles:	50000
Opt. Ambient	25 °C
Temperature :	



Synergy 21 LED Flex Strip red DC24V 24W IP20

SMD2835

Voltage: 24V, max.1A Watt: 24W±10% Light colour: red

Beam angle: 120° Protection class: IP20

Number of LEDs: 300*3528SMD Dimensions: 5000*8*3 mm

PCB colour: white, open cable end Operating temperature: -25°C to +40°C

Weight: 0.090 kg

Can be shortened every 6 LEDs Adhesive tape: yes 3M on the back

kWh/1000h: 24

Strip can be shortened at the cut marks with sharp scissors. !Attention! Strip must first be checked for functionality. Only split the strip when no current is present.

Our 3M adhesive tape adheres well, but should only be used as a mounting aid.

There are a variety of mounting options, such as clips, permanently elastic mounting adhesive, cable ties, etc.



Part No.: 133000 Vendor Part No.: S21-LED-F00098

Please note that LED strips must also be cooled.

Make sure that the LED strip does not exceed a working temperature of 40°C, otherwise its service life cannot be guaranteed.

No guarantee can be given for overheated LED strips

Attributes

Attribute	Value
Abstrahlwinkel:	120
Ampere:	1
CC oder CV:	CV
Dimmbar:	abhängig vom Netzteil
Länge:	5
LED Strip Klebeband:	ja
LED Strip Breite:	8
LED Strip Höhe:	3
LED Strip Klebeband:	ja
LED Strip kürzbar:	100
LED Strip Länge:	5000
Lichtfarbe:	rot
Lichtfarbe Name:	rot
Schutzklasse:	IP20
Volt:	24
Weight:	0.09 Kg

Additional Images

SYNERGY 21

Part No.: 133000

Vendor Part No.: S21-LED-F00098



SYNERGY 21

Part No.: 133000 Vendor Part No.: S21-LED-F00098

Accessories

Part No. Name

174020 Synergy 21 Power supply - 24V 100W BILTON