SYNERGY 21

Synergy 21 LED Flex Strip COB - NW DC24V 40W CRI>90 SLIM V2

kwh/1000h:	57,50
Lumens:	3880
Watt:	40,0
Nominal Service Life:	35000 Std.
Switching Cycles:	50000
Opt. Ambient Temperature.:	25 °C

4 0 3 8 8 1 6 1 4 4 7 9 9

Synergy 21 LED Flex Strip with COB chip - **SLIM 4mm wide and 2mm high**

Length: 5m
Voltage: 24V DC
Watt: 8W/m, 40W
Light colour: neutral white; , 4000K, CRI>90
Brightness: 776lm/m Total: 3880lm
SDCM<3
Protection class: IP20
Number of LEDs: 480/m, total: 2400LEDs
Coolable every 50mm
Dimension: 5000*4*2mm
Adhesive tape: yes 3M on the back

Strip can be cut at the cut marks with sharp scissors.
!Attention! Strip must be checked for functionality beforehand.
Only split the strip when there is no power.

Our 3M adhesive tape adheres well, but is still only to be regarded as a mounting aid. There are a variety of mounting options, such as clips, permanently elastic mounting adhesive, cable ties, etc.

Please note that LED strips must also be cooled.
Make sure that the LED strip does not exceed the operating temperature of 40°C, otherwise the service life cannot be guaranteed. No guarantee can be given for overheated LED Strips.

www.synergy21.de

Synergy21 - A Brand of ALLNET GmbH - Maistraße 2 - 82110 Germering - synergy21@allnet.de - 089 / 894 222 22
Errors and technical changes that serve the interests of progress or development of the product, are reserved.

Page 1/3

SYNERGY 21

Attributes

Attribute	Value
Abstrahlwinkel:	120
Ampere:	1.60
Betriebstemperatur:	-20 bis +50
CC oder CV:	CV
CRI:	>90
Dimmbar:	Ja
LED Strip Klebeband:	Ja
LED Strip Breite:	4mm
LED Strip Höhe:	2mm
LED Strip kürzbar:	50mm
LED Strip Länge:	5000mm
Lichtfarbe:	neutralweiß
Lichtfarbe in Kelvin:	4000
Lumen:	3880
Lumen-Effizienz:	97
Schutzklasse:	IP20
Volt:	24
Weight:	0.2 Kg
Warranty:	60.00 Months

Additional Images

www.synergy21.de

Synergy21 - A Brand of ALLNET GmbH - Maistraße 2 - 82110 Germering - synergy21@allnet.de - 089 / 894 222 22
Errors and technical changes that serve the interests of progress or development of the product, are reserved.

Page 2/3

Dimension

FPC copper:3OZ

4mm

50mm   Cables length 150mm

2mm

Errors and technical changes that serve the interests of progress or development of the product, are reserved.