

DALI MCU Tunable White | Light management systems



Areas of application

- Conference rooms
- Restaurants
- Shop lighting
- Private homes

Product benefits

- Intuitive manual dimming, switching and changing of colour temperature
- Individual setting of minimal brightness level
- Individual setting of colour temperature range

Product features

- Up to 4 DALI MCUs can be connected in parallel to set up multiple control points
- Automatic synchronization between the control points
- Cover and rotary switch in neutral white
- Length of the DALI control cable: up to 300 m


Product datasheet

Technical data

Electrical data

Nominal voltage	230 V
-----------------	-------

Dimensions & weight



Length	80.0 mm
Height	50.0 mm
Product weight	98.00 g

Colors & materials

Product color	White
---------------	-------

Temperatures & operating conditions

Ambient temperature range	0...+50 °C
---------------------------	------------

Capabilities

Dimmable	Yes
Dimming interface	DALI
Number of control outputs	1
Type of installation	Integrated in flush device box

Certificates & standards





Type of protection	IP20
Protection class	II

Equipment / Accessories

- Suitable for up to 25 electronic control gears
- Cover and rotary knob included

Product datasheet

Download Data

File	
	User instruction 726866_DALI MCU TW - mounting instruction
	User instruction 726867_User instruction DALI MCU TW
	Brochures 730792_Light is universal - Easy installation of efficient complete systems (DE)
	Brochures 730791_Light is universal - Easy installation of efficient complete systems (EN)

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899465916		Shipping carton box 15	440 mm x 210 mm x 140 mm	12.94 dm ³	2113.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.