Part No.: 198487 Vendor Part No.: S21-LED-B220016

Synergy 21 LED Flex Strip 140 SWW DC24V 75W IP68



O EN	ERG*
Synergy 21 S21-LED-B220016	
Α	
В	
C	
D	
E	
F	Œ
G	
79 kWh/1000h	2019/2015

kwh/1000h:	79,20
Lumens:	5975
Watt:	72,0
Nominal Service Life:	35000 Std.
Switching Cycles:	50000
Opt. Ambient	25 °C
Temperature.:	



Synergy 21 LED Flex Strip 2835 2835 LED Chip

Length: 5m Voltage: 24V Watt: 15W/m, 75W

Light colour: super-warm white, 2500K, CRI>90

Colour shift towards 2700K possible due to IP68 protective jacket

Brightness: 1100lm/m Total: 5500lm

Beam angle: 120° Protection class: IP68

Number of LEDs: 140*2835SMD/m, total: 700LEDs

Dimensions: 5000*13*3mm

Operating temperature: -25°C to +40°C Can be shortened every 7 LEDs 50mm Adhesive tape: yes 3M on the back

Energy efficiency class: A

kWh/1000h: 79.2

Strip can be shortened at the cut marks with sharp scissors. !Attention! Strip must be checked for functionality beforehand. Only split the strip when no current is present.

Our 3M adhesive tape adheres well, but should only be used as a mounting aid.



Part No.: 198487 Vendor Part No.: S21-LED-B220016

There are a variety of mounting options, such as clips, permanently elastic mounting adhesive, cable ties, etc.

Please note that LED strips must also be cooled.

Make sure that the LED strip does not exceed a working temperature of 40°C, otherwise its service life cannot be guaranteed.

No guarantee can be given for overheated LED strips.

Fig. similar

Attributes


Attribute	Value
Abstrahlwinkel:	120
Ampere:	3
CC oder CV:	CV
CRI:	>90
Dimmbar:	abhängig vom Netzteil
LED Strip Klebeband:	ja
LED Strip Breite:	8
LED Strip Höhe:	3
LED Strip kürzbar:	50
LED Strip Länge:	5000
Lichtfarbe:	warmweiß
Lichtfarbe in Kelvin:	2500
Lumen:	5975
Schutzklasse:	IP68
Volt:	24
Weight:	0.2 Kg
Warranty:	60.00 Months

Additional Images

SYNERGY 21

Part No.: 198487 Vendor Part No.: S21-LED-B220016





Accessories

Part No.	Name
93682	Mean Well Power Supply - 24V 150W Dimmable IP65